



Mobile Performance Meets Style and Versatility

The Vivitek D530 and D535 digital projectors are distinctive in design, lightweight and packed with user-friendly features. Connectivity options for the D530/D535 including HDMI v1.3 and both projectors are 3D-ready, make them ready for the latest multimedia applications. With a high brightness level of 3200 lumens and a weight of only 4.2 lbs, the Vivitek D530 and D535 are the portable solutions to deliver sharp, vibrant pictures and presentations.

Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- High-efficiency lamps that last up to 4000 hours (in economy mode)
- Native SVGA/XGA Resolution and able to display up to UXGA (1600 x 1200)
- Keypad lock feature to avoid accidental change to the setting
- Closed caption and 3D-ready
- Rapid on/off feature
- Enhanced color and display adjustments
- 3200 lumens of brightness with a 2300:1 contrast

| Specifications | |
|------------------------|---|
| Brightness | 3200 Lumens |
| Native Resolution | D530: SVGA (800 x 600), D535: XGA (1024 x 768) |
| Max. Resolution | UXGA (1600 x 1200) |
| Contrast Ratio | 3000:1 (Full On/Off) |
| Lamp Life and Type | ≈3000/4000 Hours (Standard/Economy Mode), 240W |
| Lamp Part # | 5811116310 |
| Display Type | Single 0.55" DLP® Technology by Texas Instruments |
| Throw Ratio | 1.93 to 2.16:1 (Distance/Width) |
| Image Size (Diagonal) | 23" to 255" (0.6 to 6.5 m) |
| Projection Distance | 3' to 30' (0.9 to 9.1 m) |
| Projection Lens | F= 2.52–2.73, f= 21.8–24 mm |
| Zoom Ratio | 1.1:1 Manual Zoom/Focus |
| Aspect Ratio | 4:3 Native, 16:9 Compatible |
| Offset | 114% |
| Keystone Correction | ±30° Vertical |
| Color Spectrum | 1.07 Billion |
| Horizontal Scan Rate | 15, 30 to 91.4 KHz |
| Vertical Scan Rate | 43 to 87 Hz |
| Speaker | 2 Watt |
| Remote Control | Card Type IR Remote |
| Projection Method | Table Top or Ceiling Mount (Front or Rear) |
| Uniformity | 85% |
| Computer Compatibility | UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible |
| Video Compatibility | SDTV (480i), EDTV (480p), HDTV (576i, 720p, 1080i) thru RGB, NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM |
| I/O Connection Ports | HDMI v1.3, VGA-In, Composite Video, S-Video, Audio RCA L/R, Audio Mini-Jack, RS-232c, USB (Service) |
| Security | Kensington® Lock Port |
| Weight | 4.2 lbs (1.9 Kg) |
| Dimensions (W x H x D) | 10.3" x 3.0" x 7.8" (261.6 x 76.2 x 198.1 mm) |
| Noise Level | 35dB/29dB (Standard/Economy Mode) |
| Power | Supply: AC 100-240V Consumption: 180W (Economy Mode), 240W (Standard Mode), <1W (Standby Mode) |
| Operating Temperature | 41 to 104°F (5 to 40°C) |
| Warranty | 1-Year Limited Warranty, 90-Day Lamp Warranty |
| Standard Accessories | AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual(CD), Lens Cap, Warranty Card |
| Optional Accessories | Replacement Lamp, Remote, Carrying Case |
| UPC | 8 14964 33466 4/8 14964 33467 1 (D530/D535) |

