

PJ1173

High Brightness Multimedia Projector



Optional Accessories

Replacement lamp.....RLC-038

Screen size [inch (m)]	4:3 screen			
	Projection distance [m (inch)]		Screen height [cm (inch)]	
	min.	max.	down	up
30 (0.8)	0.9 (35)	1.1 (42)	5 (2)	41 (16)
60 (1.5)	1.8 (71)	2.2 (86)	9 (4)	82 (32)
80 (2.0)	2.4 (96)	2.9 (115)	12 (5)	110 (43)
100 (2.5)	3.0 (120)	3.7 (144)	15 (6)	137 (54)
200 (5.1)	6.1 (241)	7.4 (291)	30 (12)	274 (108)
300 (7.6)	9.2 (363)	11.1 (437)	46 (18)	411 (162)
350 (8.9)	10.8 (424)	13.0 (510)	53 (21)	480 (189)

Screen size [inch (m)]	16:9 screen			
	Projection distance [m (inch)]		Screen height [cm (inch)]	
	min.	max.	down	up
30 (0.8)	1.0 (38)	1.2 (46)	-1 (0)	39 (15)
60 (1.5)	2.0 (78)	2.4 (94)	-2 (-1)	77 (30)
80 (2.0)	2.6 (104)	3.2 (126)	-3 (-1)	103 (41)
100 (2.5)	3.3 (131)	4.0 (157)	-4 (-2)	129 (51)
200 (5.1)	6.7 (263)	8.0 (317)	-8 (-3)	257 (101)
300 (7.6)	10.0 (395)	12.1 (476)	-12 (-5)	386 (152)
350 (8.9)	11.7 (462)	14.1 (556)	-15 (-6)	450 (177)

Model No.VS12109

PROJECTOR	Type	0.8 inches (x3) Poly-Si TFT with Micro Lens	
	Resolution	XGA 1024X768	
	Lens	Manual zoom/focus (1:1.2X)	
	Support Resolution	1600X1200 (compressed)	
DISPLAY	Keystone	Vertical Digital keystone correction: / 40 degrees	
	Size	30"-500" (Diagonal)	
	Throw Distance	0.87m-15.2m	
	Throw Ratio	1.97(wide) & 2.16(tele)	
	Lamp	275 watt ACHID	
	Brightness	5000 Lumens	
	Contrast Ratio	1000:1	
COLOR GAMUT	Aspect Ratio	4:3 & 16:9	
		98% NTSC (1931 CIE)	
AUDIO	Speakers	4w X4 Stereo	
INPUT SIGNAL	RGB	RGB analog	
	Video	NTSC, PAL, SECAM	
	HDTV Signal	HDTV (480i/p, 576i/p, 720p, 1080i)	
	Frequency	Fh:31-92 KHz, Fv:56-120 Hz	
COMPATIBILITY	PC	VGA to UXGA	
	Mac	Up to 832X624 (may require Mac Adapter)	
CONNECTOR	RGB Input	15-pin D-sub (X1) ,5-BNC x 1	
	RGB Output	15-pin D-sub (X1)	
	Digital Input	HDMI 1.3 (X1) (support with HDCP compliance)	
	Composite Video	RCA Jack X 1	
	S-Video	Mini-Din 4-pin X 1	
	Componet Video	RCA Jack (X1 set)	
	Audio Input	3.5 mm Stereo Mini Jack (X2) for RGB, RCA (L/R) Jack (X1) for Video	
	Audio Output	3.5 mm Stereo Mini Jack (X1)	
	Control	RS-232 (9 Pin D-sub) X1 ,RJ45	
	USB	Type B (for mouse control only) X1	
	POWER	Voltage	90-120VAC/220-240VAC(Auto Switching), 50/60Hz (universal)
		Consumption	460W (Typical)
NOISE LEVEL		36dB (Typical)	
LANGUAGE	LANGUAGE	English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Traditional Chinese, Turkish	
CONTROLS	Basic	Standby/On, input, menu	
	Remote	Brightness, Contrast, Gamma, Color Temp, Color, Tint, Sharpness, Active Iris, My Memory, Aspect, Over Scan, V position, H position, H Phase, H size, Auto Adjust Execute, Progressive, Video NR, 3D-YCS, Color Space, Component, Video Format, HDMI, Frame Lock, RGB IN, Resolution, Auto Keystone Execute, Keystone V, Keystone H, Whisper, Mirror, Volume, Treble, Bass, SRS WOW, Speaker, Audio, HDMI Audio, Language, Menu Position, Blank, Start up, Myscreen, Myscreen Lock, Message, Source Name, Auto Search, Auto Keystone, Auto On, Auto off, Lamp time, Filter Time, My Button, Service (Fan Speed, Auto Adjust, Ghost, Filter Message, Lens Type, Key Lock, Remote Receiv, Remote FREQ., Information, Factory Reset), Security (Security password change, Myscreen password change, PIN Lock, Transition Detector), Network (DHCP, IP address, Subnet mask, Default gateway, Time difference, Date and time, e-shot, Information, Service)	
OPERATING CONDITION	Temperature	5°C - 35°C 41°F - 95°F	
	Humidity	10% - 85% non-condensing	
DIMENSIONS (W x D x H)	Physical (mm)	418mm X 319mm X 139mm	
		16.45" X 12.56" X 5.47"	
WEIGHT	Net	7.1 kgs (15.61 lbs)	
REGULATIONS		UL60950-1/C-UL, FCC part 15 Class B, CE marking EN61000-3-2, EN61000-3-3, EN55022, EN55024 (EMC directive), DEMKO-GS, WEEE, RoHS, C-Tick (Australia / New Zealand)	

Headquarters:
381 Brea Canyon Road,
Walnut, CA 91789-0708
www.viewsonic.com

Asia Pacific
9F, No. 192, Lien Chen Road,
Chung Ho, 235 Taipei, Taiwan, R.O.C
www.viewsonic.com.tw/

ViewSonic Korea
#907, 9F, Hyundai HYEL, 2-36,
Hangangro 2-ga,
Yongsan-gu, Seoul, Korea 140-871
kr.viewsonic.com

ViewSonic Singapore
221 Henderson Road,
#04-08 Henderson Building,
Singapore 159557
www.viewsonic.com.sg/

ViewSonic Australia
Unit 4, 44 Dickson Ave, Artamon,
NSW 2064, Australia
www.viewsonic.com.au/

ViewSonic India
M-28, Commercial Complex (M-Block Market),
3rd floor, Greater Kallash-II, N Delhi - 110 048, India
in.viewsonic.com

ViewSonic Middle East
LOB 13 Office 8, PO Box 17625,
Jebel Ali, Dubai, U.A.E.
http://ap.viewsonic.com/mef/

ViewSonic®
See the difference™ 