

# StarBoard™ T-17SXL Interactive Display



The StarBoard™ T-17SXL is the latest interactive system from Hitachi Software Engineering America for annotating presentations and running computer based applications in meetings, classrooms, videoconferences, trade shows and symposiums.

The StarBoard™ T-17SXL is a pen-driven 17" TFT display that allows users to operate or annotate any software application running on a connected computer. The annotated images can be viewed on other displays such as an LCD projector or on any other StarBoard interactive display in the same location, or connected through a LAN/WAN network for remote learning or conferencing. The T-17 also features the following upgrades from its T-15 counterpart: 8 customizable function buttons for ease-of-use, and a built-in VGA/projector output for versatility.

## Deliver Effective Interactive Lessons by Facing Your Audience

The StarBoard™ T-17SXL offers an attractive presentation style and alternative for interactive whiteboards. Presenters face their audience when using the display device with the image projected onto any screen size. The concerns of blocking the audience's view, losing eye contact, and staring into glaring projector light are all resolved. The bright 17" display with SXGA resolution, provides a clear image to operate with and pinpoint accuracy in running applications or delivering interactive presentations.

## Lifetime StarBoard Support with a 2 year Manufacturer Warranty

Hitachi Software offers a full range of interactive communication systems for presentations, classrooms, and video conferences. Backed by a company known for quality products worldwide, you can trust StarBoard's reliable warranty and lifetime software support.

## StarBoard Software Brings New Life to Presentations

The appeal of the StarBoard™ T-17SXL is enhanced by the intuitive, easy-to-master StarBoard Software that allows anyone to be proficient in a matter of minutes. The pen-driven, icon oriented toolbar allows users to move from running applications to annotating over them with a single click. The main highlights of the software include the following:

- Revise, revisit, & reinforce - share, print, & save your work in a variety of universal file formats: PDF, JPEG, HTML
- Customizable toolbar - create multiple personalized toolbars
- Remote learning - conference up to 52 StarBoards
- Digital ink - 72 ink combinations: solids, highlighters, 3D, fancy, shadowed, and roller inks
- Comprehensive gallery - ready-to-go templates, graphs, maps, clip arts, math tools, & science diagrams
- Handwriting recognition - convert freehand into ASCII text
- Three powerful pens - normal drawing pens, intelli-pen converts freehand into geometric shapes, laser pen for temporary annotations
- Object management - manipulate, undo, redo, cut, copy, and paste
- List review - flip through multiple annotation sessions and programs with ease
- Video annotation - import, capture, spotlight, zoom, and annotate

T17XLP Interactive Displays Specifications		
Display characteristics	Driver type	Active-Matrix Liquid Crystal Display (TFT)
	Effective screen size	17 inches diagonal 4:3 aspect ratio
	Resolution	1280 × 1024 (SXGA)
	Pixel Pitch	0.264 × 0.264 mm
	Standard Colors	16.7 million colors
	Brightness	260 cd/m <sup>2</sup>
	Contrast Ratio	450 : 1 (type)
	Viewing Angles	Right 70°, left 70°, up 70°, down 70°
Digitizer characteristics	Input system	Electromagnetic induction
	Pen	Stylus pen (Uses one AAA alkaline dry cell; battery life: approximately 1800 hours*)
	Coordinate resolution	500 dpi
	Reading accuracy	± 0.5 mm
	Tracking speed	Approximately 125 points per second
	Interface	USB interface (USB1.1)
Input/output	Inputs	VGA Dsub 15-pin (analog RGB) Stereo mini-jack (stereo audio)
	Output	VGA Dsub 15-pin (analog RGB)
Speaker output		Stereo (1W+1W built-in amplifier)
Environmental conditions	Temperature	During use: +5 – +40°C in storage: -20 – +60°C
	Humidity	During use: 30 – 80% (no condensation); in storage: 20 – 80% (no condensation)
Power consumption / power supply		40W or less (3W or less in power saving mode) / AC adaptor Input (AC100 – 240V, 50/60 Hz, 1A) Output (DC12V, 5A)
External dimensions		395 (W) × 380 (H) × 57 (D) mm, 15.5" x 15" x 2.2" w/o stand
Weight		7 kg/ 15.4 lb
Stand adjustment		Adjustable in the range of 25° to 64°
Compatible operating systems		Windows Me/2000/XP

Specification Requirement	
CPU	Pentium2 300MHz or higher
Memory	128MB or higher
Graphic Color	High Color (16Bit or more)
Hard disk	100MB or more available space
USB Port	At least one
Operating System	Windows98/Me/2000/XP, NT4
Other Software	Internet Explorer 5.5 or higher (Internet Explorer 6.0 or higher is recommended), IME 2000/2002, PowerPoint 97-2003, DirectX8.1 (for Windows98/Me/2000), Media Player 6.4 (for Windows NT4.0)

\*\* StarBoard MAC Software is available upon request. Features will include StarBoard Pen annotation tools, Dry Erase Mode and recorder/playback functions.