



SPEC Synopsis

This 32 inch touch monitor is integrated with optical touch technology to comply with Window 7 and multi-touch application software functionalities, and to help enhance presentation experience as well as any large audience-based seminar, speech purpose. With direct-view LCD at adequate brightness, this 32 inch touch monitor shows clear sharp FHD picture and color for text and graphics, or video footage. No long will shadows be created by presenter/speaker himself due to projection, and with full emulation of mouse function, assistants are not required to aid the presenter, no more yelling "next page", presenter is in full control of his own presentation. In summary, this 32 inch touch monitor is a combination of white board and projection interactive whiteboards which serves and maximizes your investment.

**32" Optical Dual Touch LCD Monitor
Model: GT32MCQ**

Panel Size (Dia.)	32 inch
Native Resolution	1366 x 768
Max. Display Mode	1366 x 768/60Hz
Brightness	420 nits
Contrast	3000:1
View Angle	178°/178°
Response Time	6.5ms
Backlight Life	50,000 Hours
Operating Temp.	0-50°C
Operating Humid.	10-90% RH
Input Voltage	AC100~240V 50/60Hz
Power Consump.	< 100 Watts
Standby Power	< 3 Watts
Input Connector	VGA x1 , DVIx1, HDMI x 2 YPbPr x 1, audio in
Output Connector	VGAx1, YPbPr x 1, Audio out
Screen Control	RS-485 & Remote Handset
Ambient Detection	Auto Ambient Light Detection
Weight	33 kgs
Dimension (WxHxD)	820 x514 x118mm
Tempered Glass	3mm
Touch Panel	Optical Dual Touch