



## Mobility and Versatility Meets Functionality

Portable at only 3.2lbs and bright at 3000 lumens, the Vivitek D330WX projector offers a mobile and versatile presentation solution. The D330WX comes with native WXGA (widescreen) resolution, various connectivity options and quick on/off features. With DLP®/BrilliantColor™ technologies, the Vivitek D330WX delivers astounding images to be the ideal projection tool.

## Features

- Native WXGA (widescreen) resolution
- Various connectivity options, including HDMI v1.3 for digital video connections
- 3000 lumens of brightness with a 2500:1 contrast
- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Enhanced color and display adjustments
- Keypad lock feature to avoid accidental changes to the settings
- Great portability at 3.2 pounds

| Specifications         |  |
|------------------------|--|
| Brightness             | 3000 Lumens  |
| Native Resolution      | WXGA (1280 x 800)  |
| Max. Resolution        | WXGA+ (1680 x 1050)  |
| Contrast Ratio         | 2500:1 (Full On/Off)   |
| Lamp Life and Type     | ≈2000/3000 Hours (Standard/Economy Mode), 220W   |
| Lamp Part #            | TBD  |
| Display Type           | Single 0.65" DLP® Technology by Texas Instruments  |
| Throw Ratio            | 1.53 to 1.76:1 (Distance/Width)  |
| Image Size (Diagonal)  | 40" to 310" (1.0 to 7.9 m)   |
| Projection Distance    | 4.9' to 32.8' (1.5 to 10.0 m)  |
| Projection Lens        | F= 2.5, f= 21.3 ~24.5 mm   |
| Zoom Ratio             | 1.15:1 Manual Zoom/Focus   |
| Aspect Ratio           | 16:10 Native, 4:3 & 16:9 Compatible  |
| Offset                 | 123%   |
| Keystone Correction    | ±15° Vertical  |
| Color Spectrum         | 134 Million  |
| Horizontal Scan Rate   | 15, 30 to 91.4 KHz   |
| Vertical Scan Rate     | 43 to 87 Hz  |
| Speaker                | 1 Watt Mono  |
| Remote Control         | Card-Type IR Remote  |
| Projection Method      | Table Top or Ceiling Mount (Front or Rear)   |
| Uniformity             | 85%  |
| Computer Compatibility | UXGA, WXGA, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible  |
| Video Compatibility    | SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) |
| I/O Connection Ports   | HDMI v1.3, VGA-In, S-Video, Composite Video, Mini-Jack Audio-In, USB (Service)   |
| Security               | Kensington® Lock Port  |
| Weight                 | 3.2 lbs (1.45 kg)  |
| Dimensions (W x H x D) | 8.66" x 2.8" x 7.0" (220 x 71 x 178 mm)  |
| Noise Level            | 32dB/30dB (Standard/Economy Mode)  |
| Power                  | Supply: AC 100-240V, 50/60Hz<br>Consumption: 230W (Economy Mode), 280W (Standard Mode), <1W (Standby Mode)                               |
| Operating Temperature  | 41 to 95°F (5 to 35°C)   |
| Warranty               | 1-Year Limited Warranty, 90-Day Lamp Warranty  |
| Standard Accessories   | AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual, Warranty Card                              |
| Optional Accessories   | Replacement Lamp, Remote, Carrying Case  |
| UPC                    | 8 14964 33510 4  |

