

PJL3211

ViewSonic®
See the difference™ 

Light, bright and portable projector



Optional Accessories

- > Replacement lamp RLC-039
- > Universal ceiling mount WMK-005
- > Wireless G presentation gateway WPG-150

Projection Distance 4:3 Screen		Screen Size 4:3 Screen	
m	feet	m	Inch
1.2	3.9	1.0-1.2	40-47.2
1.5	4.9	1.3-1.5	50-60
1.8	5.9	1.5-1.8	60-70
2.0	6.6	1.67-2.0	65.7-78.7
3.0	9.8	2.5-3.0	98.4-118
5.0	16.4	4.17-5.0	164.2-196.8
7.8	31.5	6.4-7.6	250-300



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Headquarters:

381 Brea Canyon Road,
Walnut, CA 91789-0708
www.viewsonic.com

Asia Pacific

9F, No. 192, Lien Chen Road,
Chung Ho, 235 Taipei,
Taiwan, R.O.C
www.viewsonic.com.tw/

ViewSonic Korea

#2110, 21F Renaissance Tower Bldg,
456, Gongdeok-dong
Mapo-gu, Seoul 121-020, Korea
kr.viewsonic.com

ViewSonic Singapore

1 Kaki Bukit Road 1
#03-40 Enterprise One,
Singapore 415934
www.viewsonic.com.sg/

ViewSonic Australia

Unit 4, 44 Dickson Ave,
Artarmon,
NSW 2064, Australia
www.viewsonic.com.au/

ViewSonic India

M-28, Commercial Complex
(M-Block Market),
3rd floor, Greater Kailash-II, N Delhi
- 110 048, India
in.viewsonic.com

ViewSonic Middle East & Africa

LOB 13 Office 8, PO Box 17625,
Jebel Ali, Dubai, U.A.E.
ap.viewsonic.com/me/
ap.viewsonic.com/za/

DISPLAY	Type	0.63" (x3) Poly-Si TFT with Micro Lens	
	Resolution	XGA 1024 × 768 (native) / UXGA 1600 × 1200 (compressed)	
	Lens	1.2x Manual Optical Zoom / Manual focus	
	Keystone	Vertical Digital keystone correction: +/-30 degrees	
	Size	30" - 300" (Diagonal) / 0.8m - 7.6m	
	Throw Distance	2.62ft - 30.51ft (31" - 366")	
	Throw Ratio	1.3:1 - 1.5:1	
	Lamp	190 watt	
	Lamp life (Normal / Eco Mode)	2000 / 3000* (hours)	
	Brightness	2,500 Lumens	
	Contrast Ratio	500:1	
Aspect Ratio	4:3 (Native) / 16:9		
AUDIO	Speakers	1 x 1w @ 8Ω	
INPUT SIGNAL	Computer and Video	NTSC M(3.58MHz), 4.43MHz, PAL (B, D, G, H, I, M, N), SECAM, SD (480i/576i), ED (480p/576p), HD (720p/1080i)	
	Frequency	Fh:30 - 106 KHz, Fv:50 - 120 Hz	
COMPATIBILITY	PC	Analog: VGA to UXGA	
	Mac	Analog: Up to SXGA (may require Mac Adapter)	
CONNECTOR	RGB Input	2 × 15-pin mini D-sub	
	RGB Output	1 × 15-pin mini D-sub	
	Composite Input / output	1 × RCA jack	
	S-Video Input	1 × 4-pin mini-DIN	
	Audio Input	2 × 3.5 mini jack	
	Audio Output	1 × 3.5 mini jack	
	USB	1 × USB type B (mouse control)	
	POWER	Voltage	100~120V AC/200~240V AC(Auto Switching), 50/60Hz (universal)
	Consumption	310W (typ) / <10W (Stand-by mode)	
CONTROLS	OSD	Picture Menu: Brightness, contrast, gamma, color temp, color, tint, sharpness, My memory Image Menu: Aspect, over scan, V position, H position, H phase, H size, auto adjust execute Input Menu: Progressive, video NR, color space, video format, frame lock, computer in, resolution Setup Menu: Auto keystone execute, keystone v, whisper, mirror, volume, audio Screen Menu: Language, menu position, blank, start up, Myscreen, Myscreen lock, message, source name Option Menu: Auto search, auto keystone, auto on, auto off, lamp time, filter time, My button, service (fan speed, auto adjust, ghost, filter message, key lock, remote freq., Information, factory reset), security (security password change, Myscreen password change, PIN lock, transition detector)	
	OPERATING CONDITIONS	Temperature	5°C - 35°C (41°F - 95°F)
		Humidity	10% - 85% (non-condensing)
		Altitude	0 to + 6,000 ft
	NOISE LEVEL	Normal / Eco Mode	41dB / 34dB
	DIMENSIONS	(W x H x D, inch / mm)	274mm x 205mm x 59mm (10.8" x 8.1" x 2.3")
	WEIGHT	Net	1.85 kgs
		Gross	4.5 kgs (9.91 lb)
	REGULATIONS		UL60950-1/C-UL, FCC part 15 Class B, CE approval: EN61000-3-2, EN61000-3-3, EN55022, EN55024 (EMC directive), EN60950-1 (Low voltage directive); DEMKO-GS (Germany), WEEE, RoHS, C-Tick (AS/NZS CISPR22 Class B)(Australia / New Zealand)
	PACKAGE CONTENTS		Projector, power cable, RGB cable, RCA composite video/ audio cable, stereo mini to RCA audio adapter, remote control, soft case, lens cap, strap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
WARRANTY		3-year limited warranty on parts, and 1-year on lamp.	

For more product information, visit us on the web at www.viewsonic.com