



EDUCATION
PROJECTOR

D925TX/ D930TX



Big Pictures, Small Settings

The Vivitek D925TX/D930TX short-throw projectors are the ideal solution for small environments. The D925TX and D930TX deliver large projection performance with vivid picture quality in close-knit spaces, able to create 77" (diagonal) images from 1m distance. These projectors feature brightness level of 2600/3000 ANSI Lumens (respectively), 2400:1 contrast ratio and VividWheel III for bright and amazing color reproduction.

Features

- 2600/3000 ANSI Lumens of brightness with a 2400:1 contrast ratio
- DLP® and BrilliantColor™ technologies from Texas Instruments
- Top-loading, sliding cover for quick and easy lamp replacement
- Connectivity options include: HDMI v1.3, two (2) VGA-in, composite video, S-video
- Network-ready for integration and system administration via RJ45, and Crestron controller compliant
- VividWheel III for improved color reproduction and automatic gain control

Specifications	
Brightness (Typical)	2600/3000 ANSI Lumens (D925TX/D930TX)
Native Resolution	XGA (1024 x 768)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	2400:1 (Full On/Off)
Lamp Life and Type	D925TX: ~3000/4000 Hours (Standard/Economy Mode) D930TX: ~3000/4000 Hours (Standard/Economy Mode) 230W/280W (D925TX/D930TX)
Lamp Part #	5811100784-SU/5811100795-SU (D925TX/D930TX)
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio	0.6:1 (Distance/Width)
Image Size (Diagonal)	38" to 380" (1.0 to 9.7 m)
Projection Distance	0.5 to 5 m
Projection Lens	F=2.85, f=7.25mm
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	121%
Keystone Correction	±15° Vertical
Color Spectrum	16.7 Million
Horizontal Scan Rate	15, 30 to 90kHz
Vertical Scan Rate	43 to 85 Hz
Speaker	3W Mono
Remote Control	Full Featured IR Remote with Laser Pointer and Mouse
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i) thru RGB, NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	HDMI v1.3, VGA-In (x2), Composite Video, S-Video, RCA Audio-In, Mini-Jack Audio-In, Mini-Jack Audio-Out, VGA-Out, RS-232c, RJ45, USB (Service)
Security	Kensington® Lock Port, Security Bar
Weight	3.5 kg
Dimensions (W x H x D)	355 x 102 x 256 mm
Noise Level	D925TX: 34dB/29dB (Standard/Economy Mode) D930TX: 37dB/34dB (Standard/Economy Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption (D925TX): 240W(Economy Mode), 290W (Standard Mode), <1W (Standby Mode) Consumption (D930TX): 290W(Economy Mode), 350W (Standard Mode), <1W (Standby Mode)
Warranty	3-Year Warranty, 1-Year or 1,000h Lamp Warranty
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, Lens Cap, User's Manual (CD), Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	8 14964 33460 2 / 8 14964 33444 2 (D925TX/D930TX)

