

# PJD6221

## NETWORKABLE PORTABLE PROJECTOR – 120HZ AND 3D-READY



### Optional Accessories

- > Replacement Lamp RLC-050
- > Universal Ceiling Mount Kit WMK-005
- > Wireless G Presentation Gateway WPG-350
- > Soft Case PJ-CASE-001
- > Extended Express Exchange® PRJ-EE-08-03

Projection Distance		4:3 Screen Size			
		Wide		Tele	
M	Feet	M	Inches	M	Inches
1.5	4.92	1.17	46.14	0.99	39
1.8	5.90	1.41	55.36	1.18	47
2	6.56	1.56	61.52	1.32	52
3	9.84	2.34	92.27	1.97	78
5	16.40	3.91	153.79	3.29	130
10	32.80	7.81	307.58	6.58	259



ViewSonic Corporation's OMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

\*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved [14502-00B-08/09] PJD6221-1

DISPLAY	Type	0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024x768 (Native) / SXGA 1280x1024 (compressed)
	Lens	1.2x Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Size	30"–300" / 0.8m–7.6m
	Throw Distance	1.2m–10m / 3.9ft. – 32.8ft.
	Throw Ratio	1.6:1–1.9:1
	Lamp	180 watt
	Lamp Life (Normal / Eco-mode)	3500 / 5000* hours
	Brightness	2,700 Lumens
	Contrast Ratio	2800:1 (dynamic)
	Aspect Ratio	4:3 (native) and 16:9
	Color Depth	24 bits, 16.7M colors (8+8+8)
	Color Wheel	6-Seg RGBCYW / 7200rpm
	Color Gamut	85% NTSC 1931 CIE

INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and 576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps), HD 720p, 1080i (24fps, 25fps and 30fps)
	Frequency	Fh: 31–100KHz, Fv: 50–120Hz

COMPATIBILITY	PC	VGA to SXGA
	Mac®	Up to 1152x864 (scaled)

CONNECTOR	RGB Input	15-pin mini D-sub (x2)
	RGB Output	15-pin mini D-sub
	Composite Input	RCA jack
	S-video Input	4-pin mini-DIN
	Audio Input	3.5mm mini jack (x2)
	Audio Output	3.5mm mini jack
	Control	RS-232 (9-pin D-sub) / RJ-45
	USB	Type B (mouse control)

AUDIO	Speaker	2W
	Voltage	90~240VAC (Auto Switching), 50/60Hz (universal)

POWER	Consumption	235W (typ) / <1W (stand-by mode)
	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source

CONTROLS	OSD	Picture: brightest, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma, 3D sync, 3D sync invert Computer Image: Frequency, tracking, H. position, V. position Video Image: Saturation, sharpness, tint Setting: Menu position, projection, signal type, lamp hour, lamp hour reset, filter mode, filter hours, filter hours reset, power saving, auto source, eco-mode, high altitude, OSD timeout Advance: blank screen, password, screen capture, start up screen Text shot: digital zoom, dynamic contrast ratio, close caption, BrilliantColor
	OPERATING CONDITIONS	Temperature: 32°F–104°F (0°C–40°C) Humidity: 10%–90% (non-condensing) Altitude: 0–6,000 ft (1,800m), operational up to 10,000 ft (3,048m)

NOISE LEVEL	Normal / Eco-mode	31dB / 29dB
	DIMENSIONS (W x H x D)	Physical: 11 x 4.5 x 8.6 (in) / 280 x 114 x 218 (mm) Packaging: 13.6 x 8.7 x 12 (in) / 345 x 305 x 220 (mm)

WEIGHT	Net	5.86 lb (2.66 kg)
	REGULATIONS	CB, RoHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM, PSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC

PACKAGE CONTENTS	ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)	
	WARRANTY	3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.

**ViewSonic®**  
See the difference® 

For more product information, visit us on the web at ViewSonic.com