

Pro8200

1080P DLP® PROJECTOR – PROFESSIONAL GRADE HOME THEATER



Optional Accessories

- > Replacement Lamp RLC-061
- > Universal Ceiling Mount Kit WMK-005
- > Wireless G Presentation Gateway WPG-360
- > Extended Express Exchange® PRJ-EE-08-03

Projection Distance	4:3 Aspect				
	Wide		Tele		
M	Feet	M	Inches	M	Inches
1.5	4.92	1.22	47.8	0.81	31.8
1.8	5.90	1.49	57.4	0.97	38.1
2	6.56	1.62	63.7	1.08	42.4
3	9.84	2.44	95.8	1.61	63.7
5	16.40	4.05	159.5	2.69	106.0
10	32.80	8.11	319.0	5.39	212.1



ViewSonic Corporation's OMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications and availability subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved [15223-02B-12/10] Pro8200-1

DISPLAY	Type	0.66" Digital Micromirror Device (DLP™)	
	Resolution	1920x1080 (1080p)	
	Lens	1.5x Manual optical zoom / Manual optical focus	
	Keystone	Vertical digital keystone correction: +/- 20 degrees	
	Size	30"–300" / 0.76m–7.6m	
	Throw Distance	0.9m–10m / 3ft–32.8ft	
	Throw Ratio	1.4 – 2.14:1	
	Lamp	230 watt	
	Lamp Life (Normal / Eco-mode)	4000 / 6000* hours	
	Brightness	2000 Lumens	
	Contrast Ratio	4000:1 (dynamic)	
	Aspect Ratio	16:9 (native), 4:3, 16:10, Auto	
	Color Gamut	70% NTSC 1931 CIE	
	INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, K, L, L), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i and 1080p
Frequency		Fh: 30–100KHz, Fv: 50–85Hz	
COMPATIBILITY	PC	VGA to 1080p	
	Mac®	Up to 1080p	
CONNECTOR	RGB Input	15-pin mini D-sub (x2)	
	RGB Output	15-pin mini D-sub	
	Digital Input	HDMI 1.3 (x2)	
	Component	RCA (x3)	
	Composite Input	RCA jack	
	S-video Input	4-pin mini-DIN	
	Audio Input	3.5mm mini jack (x2), RCA (L/R) x1	
	Audio Output	3.5mm mini jack	
	Mic Input	3.5mm mini jack	
	Control	RS-232 (DB-9)	
	Screen Trigger	3.5mm (12V/1A)	
	USB	Type A for firmware update	
	AUDIO POWER	Speaker	10W (x2)
		Voltage	100–240VAC (Auto Switching), 50/60Hz (universal)
CONTROLS	Consumption	310W (max) / <1W (stand-by mode)	
	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, enter, source	
OPERATING CONDITIONS	OSD	Picture: Color Mode, Brightness, Contrast, Video Setting, Color Setting, User Color, Gamma Video/Audio: Frequency, Tracking, H Position, V Position, Overscan, Noise Reduction, Audio Setting, Microphone Volume, Speaker Volume, Mute Setting: Auto Keystone, Keystone, Aspect Ratio, Projection, Auto Source, Signal Type, Eco-mode, Filter Mode, High Altitude, Quick Power ON, Quick Cooling, DC 12V Trigger Information: Input Source, Resolution, H Frequency, V Frequency, Filter Hours, Filter Hours Reset, Equivalent Lamp Hours, Equivalent Lamp Hours Reset, Factory Default Option: Blank Screen, Password, OSD Setting, Closed Caption, Others, Display Type, Swap, Function	
	Temperature	32°F–104°F (0°C–40°C)	
	Humidity	10%–90% (non-condensing)	
	Altitude	0–6,000 ft (1,800m), operational up to 10,000 ft (3048m)	
	NOISE LEVEL	Normal / Eco-mode	31dB / 27dB
		DIMENSIONS (W x H x D)	Physical
	WEIGHT	Packaging	16.3 × 14.8 × 7.5 (in) / 414 × 375.9 × 190.5 (mm)
		Net	8.5 lb (3.86 kg)
	REGULATIONS	Gross	11.8 lb (5.36 kg)
		REGULATIONS	CB, RoHS, SVHC, WEEE, UL/cUL, FCC-B, ICES-004, TUV-S (Argentina), NOM, PSB, C-tick, KC, CE, GOST-R, Hygienic, UKrSEPRO, CCC
	PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, HDMI cable, remote control/laser with batteries, lens cap, Quick Start Guide, ViewSonic Wizard DVD (with User Guide)
	WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com